



Unshielded Discrete Distribution Module Panel, SL, 1U, 24 port, Black

## Product Classification

|                              |                                                                     |
|------------------------------|---------------------------------------------------------------------|
| <b>Regional Availability</b> | Asia   Australia/New Zealand   EMEA   Latin America   North America |
| <b>Portfolio</b>             | CommScope®                                                          |
| <b>Product Type</b>          | RJ45 patch panel                                                    |
| <b>Product Series</b>        | SL Series                                                           |

## General Specifications

|                              |            |
|------------------------------|------------|
| <b>Cable Type</b>            | Unshielded |
| <b>Color</b>                 | Black      |
| <b>Modules, quantity</b>     | 0          |
| <b>Panel Style</b>           | Straight   |
| <b>Rack Type</b>             | EIA 19 in  |
| <b>Rack Units</b>            | 1          |
| <b>Total Ports, quantity</b> | 24         |

## Dimensions

|                                     |                    |
|-------------------------------------|--------------------|
| <b>Height</b>                       | 44.45 mm   1.75 in |
| <b>Width</b>                        | 482.6 mm   19 in   |
| <b>Depth, with cable management</b> | 119.38 mm   4.7 in |

## Material Specifications

|                      |                                                                   |
|----------------------|-------------------------------------------------------------------|
| <b>Material Type</b> | High-impact, flame retardant, thermoplastic   Powder-coated steel |
|----------------------|-------------------------------------------------------------------|

## Environmental Specifications

|                              |                                      |
|------------------------------|--------------------------------------|
| <b>Operating Temperature</b> | -10 °C to +60 °C (+14 °F to +140 °F) |
| <b>Storage Temperature</b>   | -40 °C to +70 °C (-40 °F to +158 °F) |
| <b>Flammability Rating</b>   | UL 94 V-0                            |

**Safety Standard** RCM | UL | cUL

Packaging and Weights

**Packaging Material** Eco-friendly, single-use plastics-free

**Packaging quantity** 1

Regulatory Compliance/Certifications

| Agency        | Classification                                                                                                                 |
|---------------|--------------------------------------------------------------------------------------------------------------------------------|
| CHINA-ROHS    | Below maximum concentration value                                                                                              |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system                                                 |
| REACH-SVHC    | Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a> |
| ROHS          | Compliant                                                                                                                      |
| UK-ROHS       | Compliant                                                                                                                      |

