


FEATURED



Mini-Com® Aqua SC, Multimode Simplex, Black Module

CMSAQSCZBL

The Mini-Com® Multimode Simplex SC Adapter is a small form factor (SFF) adapter with integrated panel retention clips and are TIA/EIA-605 FOCIS-10 compatible. It connects two SC connectors in one module space and features an aqua SC simplex fiber adapter along with a black module and has zirconia split sleeves.

Specifications

Sub Brand	Mini-Com®
Body Style	Simplex
Fiber Type	OM4
Split Sleeve Material	Zirconia Ceramic
Overall Length (In.)	1.93
Overall Length (mm)	49
Maximum Operating Temperature (°C)	60
Maximum Operating Temperature (°F)	140
Minimum Operating Temperature (°C)	0
Minimum Operating Temperature (°F)	32
Maximum Installation Temperature (°C)	60
Maximum Installation Temperature (°F)	140
Minimum Installation Temperature (°C)	0
Minimum Installation Temperature (°F)	32
Standards Met	TIA/EIA-604 FOCIS-3 compliant adapters, Exceed TIA/EIA-568-B.3 requirements. RoHS Compliant, TIA/EIA-568-B.3 requirements
Product Type	SC Adapter Module
Application	SC adapters provide a robust solution for LANs, public networks, storage area networks and fiber-to-the-desk applications. SC adapters can also be mounted in high-density applications within Opticom® QuickNet™ Pre-Terminated MTP* Cassettes and Fiber Enclosures, and Opticom® Fiber Adapter Panels (FAPs) and Enclosures.
Adapter Color	Aqua
Module Color	Black
Connection Type	SC

Specifications (continued)

Part Features	Integrated panel retention clip, Improved adapter protective cap design, Choice of phosphor bronze or zirconia ceramic split sleeves
---------------	--

Packaging Detail

UPC	07498337620
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0037
Std. Ctn. Qty.	10
Std. Ctn. Volume (cf)	0.0368