



Opti-Core® LC Patch Cord

FX2ELLNLNSNM002

The duplex fiber patch cord is OM3 with a 1.6mm jacket. It is Low Smoke Zero Halogen (LSZH) rated and features LC Duplex connectors. It has standard insertion loss and is 2 meters in length.

Specifications

Fiber Type	OM3
Number of Fibers	2
Connector 1 Type	LC Duplex
Connector 2 Type	LC Duplex
Sub Brand	Opti-Core®
Flammability Rating	LSZH
Insertion Loss Performance	Standard
Fiber Diameter (µm)	50
Outer Diameter (In.)	0.062
Outer Diameter (mm)	1.6
Overall Length (ft.)	6.5
Overall Length (m)	2
Cable Color	Aqua
Product Type	LC Patch Cord
Application	Provide interconnect and cross-connect of applications in entrance facilities, telecommunications rooms, data centers, at the desk and network applications to interconnect pre-terminated cassettes in main distribution, horizontal distribution, and equipment distribution areas.
Standards Met	Meets or exceeds ISO/IEC 11801, TIA/EIA-568-C.3, TIA-604-3 (FOCIS-3), TIA-604-10 (FOCIS-10)

Packaging Detail

UPC	07498392214
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0155
Std. Ctn. Qty.	10
Std. Ctn. Volume (cf)	0.1550